

**Rubber rings for metallic conveyors**

These rubber rings protect the metallic conveyor rollers and also to reduce the drag of the conveyor system while functioning.

Rubber rings are manufactured from a mixture of SBR - general use when the client doesn't ask for special characteristics.

They are resistant to water and air, in temperatures ranging from -30°C to +70°C, but cannot withstand contact with oil based products. The rubber rings cannot be used in underground mines.



<b>DIMENSIONS</b>	<b>INTERIOR DIAMETER, mm</b>	<b>108</b>
	<b>EXTERIOR DIAMETER, mm</b>	<b>180</b>
	<b>HEIGHT, mm</b>	<b>160</b>
<b>ASPECT</b>	<b>WITHOUT FAULTS</b>	

<b>CHARACTERISTICS</b>	<b>VALUE</b>
<b>BASED ON SBR</b>	
<b>HARDNESS, (°Sh A)</b>	<b>65±5</b>
<b>TENSILE STRENGTH, (kgf/cm<sup>2</sup>)</b>	<b>90</b>
<b>ELONGATION AT BREAK, (%)</b>	<b>200</b>
<b>DENSITY, (g/cm<sup>3</sup>)</b>	<b>1.3</b>

For more information, prices and technical support please visit our website at [www.artego.ro](http://www.artego.ro)

E-mail us at [export@artego.ro](mailto:export@artego.ro)

Phone: +40 253 226 160

Fax: +40 253 226 160